## NSN 5910-01-232-6457

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-232-6457 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Length:** 0.150 inches **Body Width:** 0.150 inches **Body Height:** 0.100 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.100 inches **Terminal Diameter:** Between 0.017 inches and 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 5826-01-021-3289 direction finde **Capacitance Value Per Section:** 15.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -220.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0 to 30.0 single section **Tolerance Range Per Section:** -2.00 to 2.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 10000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.500 **Terminal Surface Treatment:** Solder

2 uninsulated wire lead

**Terminal Type And Quantity:** 

## NSN 5910-01-232-6457

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



She	lt L	ite:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0