NSN 5910-01-233-9280

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-233-9280

Body Style: W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.660 inches **Body Length:** 0.120 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.375 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 0.010 microfarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -56.0/+22.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 150000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.000 **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-11015/12 government specification

Shelf Life:

N/a

NSN 5910-01-233-9280

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0