NSN 5910-01-233-9286

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-233-9286
Body Style:
W/o mtg facilities, axial terminals
Mil-std-1276 Wire Lead Type Designator:
N-2
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.235 inches
Body Length:
0.687 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Burn in and hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
250000.0 megohms
Capacitance Value Per Section:
0.001 microfarads single section
Nonderated Operating Temp:
Between -62.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
5000000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.030
Case Insulation Material:
Plastic
Precious Material And Location:
Terminal surfaces gold
Terminal Type And Quantity:
2 uninsulated wire lead

N/a

Shelf Life:

NSN 5910-01-233-9286

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0