

View Online at https://aerobasegroup.com/nsn/5910-01-233-9288

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

#### **Terminal Length:**

1.625 inches

#### **Body Diameter:**

1.032 inches

**Body Length:** 

2.687 inches

**Terminal Diameter:** 

0.032 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

## **Capacitance Value Per Section:**

3.300 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

1.000

# **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

# **Specification Data:**

81349-mil-c-39022/2 government specification



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0