NSN 5910-01-234-1315

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-234-1315

Rody	Style:
Douv	Style.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

0.063 inches 0.063 inches 0.063 inches

Body Diameter:

1.453 inches

Body Length:

3.750 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.500 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Capacitance Value Per Section:

6200.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

5256.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

55.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dc Leakage At Reference Temp:

875.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded hole

NSN 5910-01-234-1315

Electrolytic Fixed Capacitor - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0