Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-234-4749

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.219 inches

#### **Body Length:**

0.608 inches

**Terminal Diameter:** 

0.025 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### **Electrical Polarization:**

Nonpolarized

## Capacitance Value Per Section:

10.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### Tolerance Range Per Section:

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

## **Capacitive Electrode Material:**

Tantalum

#### Case Insulation Material:

Plastic

# Test Data Document:

81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

# **Specification Data:**

81349-mil-c-3965/24 government specification

# Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-01-234-4749

Electrolytic Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

