NSN 5910-01-237-1420

Body Style:

N/a

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-237-1420

| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals | | | | | | |
|---|--|--|--|--|--|--|
| Reliability Indicator: | | | | | | |
| Not establishednot established | | | | | | |
| Terminal Length: | | | | | | |
| 1.500 inches 1.500 inches 1.500 inches | | | | | | |
| Body Diameter: | | | | | | |
| 0.510 inches | | | | | | |
| Body Length: | | | | | | |
| 1.473 inches | | | | | | |
| Terminal Diameter: | | | | | | |
| 0.032 inches | | | | | | |
| Schematic Diagram Designator: | | | | | | |
| No common or grounded electrode (s) | | | | | | |
| Anode Type: | | | | | | |
| Etched foil | | | | | | |
| Electrical Polarization: | | | | | | |
| Polarized | | | | | | |
| Features Provided: | | | | | | |
| Hermetically sealed case | | | | | | |
| Capacitance Value Per Section: | | | | | | |
| 100.000 microfarads single section | | | | | | |
| Nonderated Operating Temp: | | | | | | |
| Between -40.0 degrees celsius and 85.0 degrees celsius | | | | | | |
| Nonderated Continuous Voltage Rating And Type Per Section: | | | | | | |
| 50.0 dc single section | | | | | | |
| Tolerance Range Per Section: | | | | | | |
| -10.00/+150.00 percent single section | | | | | | |
| Case Material: | | | | | | |
| Metal | | | | | | |
| Capacitive Electrode Material: | | | | | | |
| Aluminum | | | | | | |
| Dc Leakage At Reference Temp: | | | | | | |
| 0.100 milliamperes | | | | | | |
| Terminal Surface Treatment: | | | | | | |
| Solder | | | | | | |
| Case Insulation Material: | | | | | | |
| Plastic | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 2 uninsulated wire lead | | | | | | |
| Shelf Life: | | | | | | |

NSN 5910-01-237-1420

Electrolytic Fixed Capacitor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0