NSN 5910-01-237-2446

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-237-2446

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
0.787 inches 0.787 inches 0.787 inches
Body Diameter:
0.197 inches
Body Length:
0.433 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.197 inches
Terminal Diameter:
0.023 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Capacitance Value Per Section:
47.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
10.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
19.000
Dc Leakage At Reference Temp:
4.000 microamperes
Terminal Surface Treatment:

Terminal Type And Quantity:

Case Insulation Material:

2 uninsulated wire lead

Solder

Plastic

NSN 5910-01-237-2446

Electrolytic Fixed Capacitor - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0