# NSN 5910-01-237-2447

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-237-2447

## **Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not establishednot establishednot established

## Terminal Length:

2.250 inches 2.250 inches 2.250 inches

## **Body Diameter:**

0.406 inches

#### **Body Length:**

1.126 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

## Impedance At Minimum Operating Tempurature In Ohms:

24.0

## **Electrical Polarization:**

Polarized

## **Features Provided:**

Hermetically sealed case

## Capacitance Value Per Section:

220.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

40.0 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## Case Material:

Metal

**Capacitive Electrode Material:** 

Tantalum

## Equivalent Series Resistance At Reference Tempurature In Ohms:

1.40

# Dc Leakage At Reference Temp:

5.000 microamperes

# **Terminal Surface Treatment:**

Solder

# NSN 5910-01-237-2447

Electrolytic Fixed Capacitor - Page 2 of 2



**Case Insulation Material:** 

Plastic

## Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A010b0