NSN 5910-01-238-6695

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-238-6695

D ~ d	Style:
DUUV	Sivie.

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s)

Reliability Indicator:

Not establishednot established

Terminal Length:

1.000 inches 1.000 inches 1.000 inches

Body Length:

0.600 inches

Body Width:

0.375 inches

Body Height:

0.195 inches

Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

End Application:

5835-01-023-4332 recorder-reprod

Capacitance Value Per Section:

68.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Tempurature In Percent:

8.000

Dc Leakage At Reference Temp:

0.500 microamperes

Terminal Surface Treatment:

Solder

NSN 5910-01-238-6695

Electrolytic Fixed Capacitor - Page 2 of 2



Ī	erminal	Type	And	Quant	tity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0