## NSN 5910-01-238-8556

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-238-8556

Body	Style:
------	--------

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.948 inches 0.948 inches

**Body Diameter:** 

0.256 inches

**Body Length:** 

0.597 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.100 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Solid

**Electrical Polarization:** 

Polarized

**End Application:** 

6625-01-188-7441 generator, signa

**Capacitance Value Per Section:** 

6.800 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

10 000

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

13.50

Dc Leakage At Reference Temp:

5.000 microamperes

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-238-8556

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig: A010b0