NSN 5910-01-239-0109

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-239-0109

| Body Style: |
|---|
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.250 inches |
| Body Length: |
| 0.310 inches |
| Body Width: |
| 0.340 inches |
| Body Height: |
| 0.160 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.100 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| F-15 acft |
| Capacitance Value Per Section: |
| 0.470 microfarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -15.0/+15.0 without voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Insulation Resistance At Reference Temp: |
| 1000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 2.500 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 insulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5910-01-239-0109

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0