NSN 5910-01-239-2032



Ceramic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-239-2032 **Body Style:** W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.385 inches **Body Length:** 0.156 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.250 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohms **Capacitance Value Per Section:** 75.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -1500.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -250.0/+250.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 7500.0 megohms **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

Unit Of Measure:

NSN 5910-01-239-2032

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0