## NSN 5910-01-239-5778

**Body Style:** 

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-239-5778

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals
Reliability Indicator:
Not establishednot established
Terminal Length:
1.380 inches 1.380 inches 1.380 inches
Body Diameter:
0.236 inches
Body Length:
0.472 inches
Terminal Diameter:
0.024 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Etched foil
Impedance At Minimum Operating Tempurature In Ohms:
2.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
25.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
25.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
15.000
Dc Leakage At Reference Temp:
0.030 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-01-239-5778

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0