

View Online at <https://aerobasegroup.com/nsn/5910-01-239-6987>

**Body Style:**

W/thd bushing mtg, terminals on opposite end

**Reliability Indicator:**

Not established

**Width Across Flats:**

0.187 inches

**Terminal Length:**

0.610 inches

**Body Length:**

0.468 inches

**Continuous Current Rating In Amps:**

10.0

**Terminal Diameter:**

0.032 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unef

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Section Quantity:**

3

**Features Provided:**

Mounting hardware

**Capacitance Value Per Section:**

0.030 microfarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-55.0/+125.0 with rated voltage applied single section

**Nonderated Operating Temp:**

25.0 degrees celsius

**Thread Size:**

0.216 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Range Per Section:**

-0.00/+100.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

500.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

2.500

**Reference Temperature At Which Rated:**

25.0 degrees celsius

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0