## NSN 5910-01-239-8446

**Body Style:** 

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-239-8446

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:					
Not establishednot established					
Terminal Length:					
1.380 inches 1.380 inches 1.380 inches					
Body Diameter:					
0.315 inches					
Body Length:					
0.629 inches					
Terminal Diameter:					
0.024 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Anode Type:					
Etched foil					
Impedance At Minimum Operating Tempurature In Ohms:					
3.0					
Electrical Polarization:					
Polarized					
Capacitance Value Per Section:					
100.000 microfarads single section					
Nonderated Operating Temp:					
Nonderated Operating Temp:					
Nonderated Operating Temp: Between -40.0 degrees celsius and 85.0 degrees celsius					
Between -40.0 degrees celsius and 85.0 degrees celsius					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  25.0 dc single section					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  25.0 dc single section  Tolerance Range Per Section:					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  25.0 dc single section  Tolerance Range Per Section:  -20.00/+80.00 percent single section					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  25.0 dc single section  Tolerance Range Per Section:  -20.00/+80.00 percent single section  Case Material:					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  25.0 dc single section  Tolerance Range Per Section:  -20.00/+80.00 percent single section  Case Material:  Metal					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material:					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material:  Aluminum					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material:  Aluminum  Dissipation Factor At Reference Tempurature In Percent:					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material:  Aluminum  Dissipation Factor At Reference Tempurature In Percent: 10.000					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material: Aluminum  Dissipation Factor At Reference Tempurature In Percent: 10.000  Dc Leakage At Reference Temp:					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material: Aluminum  Dissipation Factor At Reference Tempurature In Percent: 10.000  Dc Leakage At Reference Temp: 3.000 microamperes					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material: Aluminum  Dissipation Factor At Reference Tempurature In Percent: 10.000  Dc Leakage At Reference Temp: 3.000 microamperes  Terminal Surface Treatment:					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material: Aluminum  Dissipation Factor At Reference Tempurature In Percent: 10.000  Dc Leakage At Reference Temp: 3.000 microamperes  Terminal Surface Treatment: Solder					
Between -40.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  25.0 dc single section  Tolerance Range Per Section: -20.00/+80.00 percent single section  Case Material:  Metal  Capacitive Electrode Material: Aluminum  Dissipation Factor At Reference Tempurature In Percent: 10.000  Dc Leakage At Reference Temp: 3.000 microamperes  Terminal Surface Treatment: Solder  Case Insulation Material:					

## NSN 5910-01-239-8446

Electrolytic Fixed Capacitor - Page 2 of 2



		fe:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0