

View Online at <https://aerobasegroup.com/nsn/5910-01-240-1804>

Body Style:

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

0.063 inches 0.063 inches 0.063 inches

Body Diameter:

1.453 inches

Body Length:

2.250 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.422 inches and 0.516 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Nimitz class cvn, wasp class lhd, spruance class d (963) , tarawa class lha, surface minesweeping systems, Forrestal class cv, avenger class mcm, Oliver Perry class ffg, Whidbey Island class LSD, Sirius class T-AFS 8

Capacitance Value Per Section:

80.000 microfarads single section

Nonrated Operating Temp:

Between -40.0 degrees Celsius and 85.0 degrees Celsius

Dc Leakage At Maximum Operating Temp:

9.5 milliamperes

Nonrated Continuous Voltage Rating And Type Per Section:

450.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

2.80

Special Features:

Weapons system essential

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0