NSN 5910-01-240-2257

Plastic Dielectric Fixed Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-01-240-2257



Body Style: W/o mtg facilities, terminal (s) on one surface Reliability Indicator: Not established **Terminal Length:** 0.750 inches **Body Length:** 2.500 inches **Body Width:** 1.188 inches **Body Height:** 3.875 inches **Center To Center Distance Between Terminals Parallel To Length:** 1.125 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **End Application:** Training set, tactical electronic warfare an/msq-t13 **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 2.000 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 15000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.000 **Terminal Surface Treatment:** Solder **Dielectric Material:**

Plastic

NSN 5910-01-240-2257

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-c-19978/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0