NSN 5910-01-240-3001

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-240-3001
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.130 inches
Body Width:
0.070 inches
Body Height:
0.070 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
360.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
Tolerance of Tempurature Obernolent Fer Dection in Figure 1 Deg Delaids.
-30.0/+30.0 single section
-30.0/+30.0 single section
-30.0/+30.0 single section Tolerance Range Per Section:
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment:
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder Terminal Type And Quantity:
-30.0/+30.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.150 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead

--

NSN 5910-01-240-3001

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0