NSN 5910-01-240-4956

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-240-4956

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Unable To Decode:

Unable to decode and unable to decode

Terminal Length:

0.250 inches

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Body Diameter:

Between 1.360 inches and 1.422 inches

Body Length:

Between 3.031 inches and 3.281 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.500 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

2 threaded mounting holes

Capacitance Value Per Section:

215.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 65.0 degrees celsius

Thread Size:

0.190 inches

Nonderated Continuous Voltage Rating And Type Per Section:

125.0 ac-rms single section

Tolerance Range Per Section:

-0.00/+44.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

NSN 5910-01-240-4956

Electrolytic Fixed Capacitor - Page 2 of 2



Power Factor At Reference Tempurature In Percent:
10.000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0