## NSN 5910-01-241-2666

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-241-2666

<b>D</b> -	٠. د	C4	٠
DU	uv	Stv	ıe:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Dummy Terminal Quantity:** 

111

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

1.000 inches 1.000 inches 1.000 inches

**Body Diameter:** 

0.635 inches

**Body Length:** 

1.124 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.300 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

0.1

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

1000.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

6.3 dc single section

**Tolerance Range Per Section:** 

-10.00/+100.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.20

Dc Leakage At Reference Temp:

4.000 microamperes

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-241-2666

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0