NSN 5910-01-241-3537

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-241-3537

Bodv	/ Stv	رام.
DOU	/ U L	vie.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot established

Terminal Length:

1.500 inches 1.500 inches 1.500 inches

Body Diameter:

0.351 inches

Body Length:

0.786 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Electrical Polarization:

Polarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

15.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

175.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Tempurature In Percent:

6.000

Dc Leakage At Reference Temp:

7.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

NSN 5910-01-241-3537

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal	Type	And	Quantity:
-----------------	-------------	-----	-----------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0