Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-241-5298

Thread Class: 2a 2a Body Style: Cylindrical Cylindrica C
Body Style:CylindricalOverall Length:2.673 inchesBushing Diameter:0.250 inchesShaft Diameter:0.250 inches single shaftBushing Length:0.250 inches0.375 inchesShaft Length:0.375 inches0.363 inches single shaftOverall Diameter:0.300 inches0.300 inchesOuting Factor At 25 Deg Celsius:1500.0Mounting Facility Screw Thread Series Designator:UnefInclosuer Type:UninclosedPlate Quantity:27Tuning Characteristic:Straight line capacity single section
CylindridalOverall Length:2.673 inchesBushing Diameter:0.250 inchesShaft Diameter:0.250 inches single shaftBushing Length:0.375 inchesShaft Length:0.375 inches single shaftOverall Diameter:0.300 inches0.301 inches0.302 inches0.303 inches single shaftOverall Diameter:0.500 inches0.301 inches0.301 inches0.302 inches0.303 inches0.303 inches0.303 inches0.304 inches0.304 inches0.305 inches1.300.0Mounting Facility Screw Thread Series Designator:1.300.11.300.21.300.3
Overall Length:2.673 inchesBushing Diameter:0.250 inchesShaft Diameter:0.250 inches single shaftBushing Length:0.375 inchesShaft Length:0.375 inches single shaftOverall Diameter:0.363 inches single shaftOverall Diameter:0.500 inches0.500 inches0.500 inchesOverall Diameter:0.500 inches0.500 inchesDiameter:0.500 inchesOutling Factor At 25 Deg Celsius:1500.0Bushing Staft Solorew Thread Series Designator:UnefInclosure Type:UnindosedPate Quantity:27Tuning Characteristic:Straight line capacity single section
2.673 inches Bushing Diameter: 0.250 inches Shaft Diameter: 0.250 inches single shaft Bushing Length: 0.375 inches Shaft Length: 0.375 inches Shaft Length: 0.563 inches single shaft Overall Diameter: 0.500 inches Cuelly Factor At 25 Deg Celsius: 1500.0 Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Bushing Diameter:0.250 inchesShaft Diameter:0.250 inches single shaftBushing Length:0.375 inchesShaft Length:0.363 inches single shaftOverall Diameter:0.500 inchesQuality Factor At 25 Deg Celsius:1500.0Mounting Facility Screw Thread Series Designator:UnefUninclosedPlate Quantity:27Tuing Characteristic:Straight line capacity single section
0.250 inches Shaft Diameter: O.250 inches single shaft Bushing Length: O.375 inches Shaft Length: O.375 inches Shaft Length: O.563 inches single shaft Overall Diameter: O.500 inches Ouality Factor At 25 Deg Celsius: 1500.0 Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Shaft Diameter:0.250 inches single shaftBushing Length:0.375 inchesShaft Length:0.563 inches single shaftOverall Diameter:0.500 inchesQuality Factor At 25 Deg Celsius:1500.0Mounting Facility Screw Thread Series Designator:UnefInclosure Type:UninclosedPlate Quantity:27Tuning Characteristic:Kraight line capacity single section
0.250 inches single shaft Bushing Length: 0.375 inches Shaft Length: 0.563 inches single shaft Overall Diameter: 0.500 inches 0.500 inches Quality Factor At 25 Deg Celsius: 1500.0 Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Bushing Length:0.375 inches0.375 inchesShaft Length:0.563 inches single shaftOverall Diameter:0.500 inchesQuality Factor At 25 Deg Celsius:1500.0Mounting Facility Screw Thread Series Designator:UnefInclosure Type:UninclosedPlate Quantity:27Tuning Characteristic:Straight line capacity single section
0.375 inches Shaft Length: 0.563 inches single shaft Overall Diameter: 0.500 inches Quality Factor At 25 Deg Celsius: Quality Factor At 25 Deg Celsius: 1500.0 Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Shaft Length:0.563 inches single shaftOverall Diameter:0.500 inchesQuality Factor At 25 Deg Celsius:1500.0Mounting Facility Screw Thread Series Designator:UnefInclosure Type:UninclosedPlate Quantity:27Tuning Characteristic:Straight line capacity single section
0.563 inches single shaft Overall Diameter: 0.500 inches Quality Factor At 25 Deg Celsius: 1500.0 Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Overall Diameter:0.500 inchesQuality Factor At 25 Deg Celsius:1500.0Mounting Facility Screw Thread Series Designator:UnefInclosure Type:UninclosedPlate Quantity:27Tuning Characteristic:Straight line capacity single section
0.500 inches Quality Factor At 25 Deg Celsius: 1500.0 Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Quality Factor At 25 Deg Celsius:1500.0Mounting Facility Screw Thread Series Designator:UnefInclosure Type:UninclosedPlate Quantity:27Tuning Characteristic:Straight line capacity single section
1500.0 Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Unef Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Inclosure Type: Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Uninclosed Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
Plate Quantity: 27 Tuning Characteristic: Straight line capacity single section
27 Tuning Characteristic: Straight line capacity single section
Tuning Characteristic: Straight line capacity single section
Straight line capacity single section
Split-stator Rotary Plate Type:
Butterfly
Bushing Shape:
Round
Mounting Facility Type And Quantity:
1 threaded bushing
Thread Size:
0.375 inches
Shaft Type:
Round, slotted single shaft
Capacitance Range In Picofarads:
+6.0/+145.0 single section
Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft



Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0