

View Online at <https://aerobasegroup.com/nsn/5910-01-242-4002>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

0.625 inches 0.625 inches 0.625 inches

**Body Diameter:**

0.216 inches

**Body Length:**

0.385 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.100 inches

**Terminal Diameter:**

0.020 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**End Application:**

5820-01-090-9304

**Capacitance Value Per Section:**

0.220 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

35.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

0.080

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0