## NSN 5910-01-243-1798

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-243-1798

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Length:** 

1.250 inches

**Unable To Decode:** 

Unable to decode and unable to decode

**Unable To Decode:** 

Unable to decode and unable to decode

**Body Length:** 

Between 0.280 inches and 0.300 inches

**Body Width:** 

Between 0.280 inches and 0.300 inches

**Body Height:** 

Between 0.080 inches and 0.100 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.185 inches and 0.215 inches

**Terminal Diameter:** 

Between 0.024 inches and 0.029 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

5840-01-084-2444 radar set

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

1.000 microfarads single section

Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-0.00/+10.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

100000.0 megohms

## NSN 5910-01-243-1798

Fiig: A010b0

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Dissipation Factor At Reference Tempurature In Percent:
2.500
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No