

View Online at https://aerobasegroup.com/nsn/5910-01-243-1798

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

### Unable To Decode:

Unable to decode and unable to decode

#### **Terminal Length:**

1.250 inches

#### Unable To Decode:

Unable to decode and unable to decode

### Unable To Decode:

Unable to decode and unable to decode

### **Body Length:**

Between 0.280 inches and 0.300 inches

#### **Body Width:**

Between 0.280 inches and 0.300 inches

#### **Body Height:**

Between 0.080 inches and 0.100 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

### **Terminal Diameter:**

Between 0.024 inches and 0.029 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **End Application:**

5840-01-084-2444 radar set

### Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

# Capacitance Value Per Section:

1.000 microfarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

# **Tolerance Range Per Section:**

-0.00/+10.00 percent single section

# Case Material:

Plastic

# Insulation Resistance At Reference Temp:

100000.0 megohms



Dissipation Factor At Reference Tempurature In Percent:

2.500

**Terminal Surface Treatment:** 

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0