## NSN 5910-01-243-4039

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-243-4039

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
5.5 millimeters 5.5 millimeters 5.5 millimeters
Body Diameter:
6.8 millimeters
Body Length:
8.5 millimeters
Center To Center Distance Between Terminals Parallel To Diameter:
2.5 millimeters
Terminal Diameter:
0.5 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Capacitance Value Per Section:
33.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
25.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
14.0000
Terminal Surface Treatment:
Solder
Case Insulation Material:

Shelf Life:

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Plastic

N/a

## NSN 5910-01-243-4039

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0