## NSN 5910-01-244-1748

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-244-1748
Body Style:
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals
Reliability Indicator:
Not establishednot established
Terminal Length:
1.500 inches 1.500 inches
Body Diameter:
0.375 inches
Body Length:
0.937 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

35.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

8.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

Dc Leakage At Reference Temp:

3.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

**Plastic** 

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-244-1748

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0