

View Online at <https://aerobasegroup.com/nsn/5910-01-244-1751>

**Reliability Indicator:**

Establishedestablished

**Reliability Failure Rate Level In Percent:**

1.00001.0000

**Terminal Length:**

0.250 inches 0.250 inches

**Body Diameter:**

0.875 inches

**Body Length:**

1.625 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.300 inches

**Terminal Diameter:**

0.040 inches

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

0.24

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

3900.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

495.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

7.0 dc single section

**Tolerance Range Per Section:**

-10.00/+50.00 percent single section

**Test Data Document:**

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 uninsulated wire lead

**Specification Data:**

81349-mil-c-39018/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0