

View Online at <https://aerobasegroup.com/nsn/5910-01-244-1751>

Reliability Indicator:

Establishedestablished

Reliability Failure Rate Level In Percent:

1.00001.0000

Terminal Length:

0.250 inches 0.250 inches

Body Diameter:

0.875 inches

Body Length:

1.625 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.300 inches

Terminal Diameter:

0.040 inches

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

0.24

Electrical Polarization:

Polarized

Capacitance Value Per Section:

3900.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

495.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

7.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Test Data Document:

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 uninsulated wire lead

Specification Data:

81349-mil-c-39018/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0