NSN 5910-01-244-4502

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-244-4502 |
|--|
| Body Style: |
| Chip type |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.001 |
| Terminal Length: |
| 0.148 inches |
| Body Length: |
| 0.092 inches |
| Body Width: |
| 0.260 inches |
| Body Height: |
| 0.128 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 10000.0 megohms |
| Capacitance Value Per Section: |
| 470.000 picofarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -25.0/+15.0 with rated voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 200.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 2.500 |
| Test Data Document: |
| 81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 printed circuit |
| Specification Data: |

N/a

Shelf Life:

81349-mil-c-39014/22 government specification

NSN 5910-01-244-4502

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0