# NSN 5910-01-244-9443

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-244-9443

# **Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

# **Reliability Indicator:**

Establishedestablishedestablished

## **Reliability Failure Rate Level In Percent:**

0.0100.0100.010

#### **Terminal Length:**

1.500 inches 1.500 inches 1.500 inches

#### **Body Diameter:**

0.185 inches

**Body Length:** 

0.474 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## **Electrical Polarization:**

Polarized

# **Capacitance Value Per Section:**

39.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## Capacitive Electrode Material:

Tantalum

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

No

## Fiig:

A010b0