Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-244-9450

## Body Style:

W/o mtg facilities, terminals on opposite surfaces

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.500 inches

Body Length:

0.420 inches

#### Body Width:

0.170 inches

**Body Height:** 

0.290 inches

**Terminal Diameter:** 

0.020 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

#### **Capacitance Value Per Section:**

0.056 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

960.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:** 

Plastic

# Insulation Resistance At Reference Temp:

10000.0 megohm-microfarads

# Dissipation Factor At Reference Tempurature In Percent:

1.000

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

# Unit Of Measure:

--

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0