## NSN 5910-01-245-1400

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-245-1400

**Body Style:** W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.730 inches **Body Length:** 0.167 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.375 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 1500.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -66.0/+22.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 1600.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material:

-----

**Plastic** 

**Insulation Resistance At Reference Temp:** 

150000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.500

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Specification Data:** 

81349-mil-c-11015/21 government specification

Shelf Life:

N/a

## NSN 5910-01-245-1400

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0