## NSN 5910-01-245-1996

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-245-1996

#### **Body Style:**

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

#### **Reliability Indicator:**

Not establishednot establishednot established

#### **Terminal Length:**

0.250 inches 0.250 inches 0.250 inches

#### **Body Diameter:**

3.020 inches

#### **Body Length:**

5.657 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

1.250 inches

**Terminal Diameter:** 

0.190 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Anode Type:

Plain foil

#### Electrical Polarization:

Polarized

#### **End Application:**

5820-01-162-3402 receiver-transm

#### Capacitance Value Per Section:

66000.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

#### Case Material:

Metal

## Capacitive Electrode Material:

Aluminum

## Equivalent Series Resistance At Reference Tempurature In Ohms:

0.0046

#### **Terminal Type And Quantity:**

2 threaded hole

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5910-01-245-1996

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0