## NSN 5910-01-245-4637

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-245-4637

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not establishednot established

### **Terminal Length:**

1.250 inches 1.250 inches 1.250 inches

**Body Diameter:** 

0.315 inches

**Body Length:** 

0.630 inches

**Terminal Diameter:** 

0.024 inches

### **Schematic Diagram Designator:**

No common or grounded electrode (s)

#### **Anode Type:**

Plain foil

### **Impedance At Minimum Operating Tempurature In Ohms:**

4.0

### **Electrical Polarization:**

Polarized

### **Capacitance Value Per Section:**

100.000 microfarads single section

#### **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:** 

Metal

### **Capacitive Electrode Material:**

Aluminum

### **Dissipation Factor At Reference Tempurature In Percent:**

0.140

### Dc Leakage At Reference Temp:

4.000 microamperes

### **Terminal Surface Treatment:**

Solder

### **Case Insulation Material:**

Plastic

### **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-01-245-4637

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0