NSN 5910-01-245-6471

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-245-6471

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
0.687 inches
Body Width:
0.218 inches
Body Height:
0.343 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.150 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
-5.00/+5.00 percent single section Case Material:
·
Case Material:
Case Material: Plastic
Case Material: Plastic Insulation Resistance At Reference Temp:
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment:
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

Fiig: A010b0