

View Online at <https://aerobasegroup.com/nsn/5910-01-245-9534>

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.813 inches

Terminal Length:

0.313 inches

Bushing Diameter:

Between 0.251 inches and 0.255 inches

Bushing Length:

0.250 inches

Body Length:

Between 0.438 inches and 0.500 inches

Overall Diameter:

0.406 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Terminal Diameter:

0.094 inches

Quality Factor At 25 Deg Celsius:

500.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Terminal Location:

Circumference on adjustment control end bent backward

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round w/flat

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Bushing Width:

Between 0.230 inches and 0.234 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Capacitance Range In Picofarads:

+1.0/+16.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Material:

Metal base

Terminal Type And Quantity:

1 tab, solder lug and 1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0