NSN 5910-01-246-0373



Ceramic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-246-0373 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.500 inches **Body Width:** 0.500 inches **Body Height:** 0.200 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.400 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 5000.0 megohms **Capacitance Value Per Section:** 1.000 microfarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -15.0/+15.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 175.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.500 **Terminal Surface Treatment:** Nickel

Dissipation Factor At Reference Tempurature In Perce
2.500
Terminal Surface Treatment:
Nickel
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:

NSN 5910-01-246-0373

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0