## NSN 5910-01-246-3510

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-246-3510 **Body Style:** Single inline **Reliability Indicator:** Not established **Terminal Length:** 0.532 inches **Body Length:** 3.125 inches **Body Width:** 1.000 inches **Body Height:** 3.125 inches Center To Center Distance Between Terminals Parallel To Length: 1.500 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 5.3 **Electrical Polarization:** Polarized **End Application:** 5820-01-145-2459 multiplexer **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 380.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 250.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp:

210.000 microamperes **Terminal Surface Treatment:** 

Solder

## NSN 5910-01-246-3510

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type And	Quantity:
-------------------	-----------

2 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0