

View Online at <https://aerobasegroup.com/nsn/5910-01-246-3627>

**Body Style:**

Piston

**Overall Length:**

0.531 inches

**Terminal Length:**

0.147 inches

**Body Length:**

0.281 inches

**Overall Diameter:**

0.145 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

0.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Center To Center Distance Between Terminals Parallel To Length:**

0.260 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.260 inches

**Quality Factor At 25 Deg Celsius:**

7500.0

**Terminal Width:**

0.030 inches

**Terminal Thickness:**

0.010 inches

**Inclosure Type:**

Encased

**Tuning Characteristic:**

Straight line frequency single section

**Adjustment Device Torque:**

Between 0.300 inch-ounces and 4.000 inch-ounces

**Insulation Dc Resistance At Max Operating Temp:**

100000.0 megohms

**Mounting Facility Type And Quantity:**

2 terminal

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Capacitance Range In Picofarads:**

+0.5/+5.0 single section

**Nonderated Voltage Rating And Type:**

250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.02 single section

**Material:**

Aluminum base and ceramic base

**Test Data Document:**

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 printed circuit

**Specification Data:**

81349-mil-c-14409/14 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0