

View Online at <https://aerobasegroup.com/nsn/5910-01-247-7380>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

0.800 inches

Body Width:

0.750 inches

Body Height:

0.275 inches

Center To Center Distance Between Terminals Parallel To Length:

0.680 inches

Terminal Diameter:

0.031 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

100.0 megohm-microfarads

Capacitance Value Per Section:

0.022 microfarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 with 500 volts applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

4000.0 dc single section

Criticality Code Justification:

Zzzy

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

2.500

Terminal Surface Treatment:

Silver

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo3901

Precious Material And Location:

Terminal surfaces silver

Terminal Type And Quantity:

2 uninsulated wire lead

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0