

View Online at https://aerobasegroup.com/nsn/5910-01-250-4697

Be	ody Style:
Cł	hip type
Re	eliability Indicator:
No	ot established
Τe	erminal Length:
0.0	020 inches
В	ody Length:
0.0	080 inches
Bo	ody Width:
0.0	050 inches
Bo	ody Height:
Be	etween 0.020 inches and 0.060 inches
Sc	chematic Diagram Designator:
No	o common or grounded electrode (s)
Ca	apacitance Value Per Section:
3.:	300 picofarads single section
No	onderated Operating Temp:
Be	etween -55.0 degrees celsius and 125.0 degrees celsius
Τe	empurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0	0 single section
No	onderated Continuous Voltage Rating And Type Per Section:
50	0.0 dc single section
Тс	olerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-3	0.0/+30.0 single section
Тс	blerance Range Per Section:
-0	.50/+0.50 picofarads single section
Ca	ase Material:
Ce	eramic
In	sulation Resistance At Reference Temp:
10	00000.0 megohms
Di	issipation Factor At Reference Tempurature In Percent:
0.	150
Te	erminal Surface Treatment:
Sc	blder
Τe	erminal Type And Quantity:
2	bonding pad
Sł	helf Life:
N/	/a
Uı	nit Of Measure:
De	emilitarization:
NI.	0

NSN 5910-01-250-4697 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

