

View Online at <https://aerobasegroup.com/nsn/5910-01-251-4368>

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.666 inches

Terminal Length:

Between 0.110 inches and 0.140 inches

Bushing Diameter:

0.190 inches

Bushing Length:

Between 0.200 inches and 0.230 inches

Body Length:

Between 0.266 inches and 0.296 inches

Overall Diameter:

Between 0.215 inches and 0.225 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-15.0/+15.0 single section

Quality Factor At 25 Deg Celsius:

10000.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Torque:

4.000 inch-pounds

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Insulation Dc Resistance At Max Operating Temp:

100000.0 megohms

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.190 inches

Capacitance Range In Picofarads:

+0.6/+6.0 single section

Nonderated Voltage Rating And Type:

500.0 dc dielectric withstanding single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.01 single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0