NSN 5910-01-251-6705

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-251-6705 **Body Style: Dual inline Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.0100 **Terminal Length:** 0.148 inches **Body Length:** 0.260 inches **Body Width:** 0.092 inches **Body Height:** 0.128 inches **Capacitance Value Per Section:** 4.700 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -120.0/+120.0 single section **Tolerance Range Per Section:** -0.50/+0.50 picofarads single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 100000.0 megohms **Test Data Document:** 81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 tab, solder lug **Specification Data:** 81349-mil-c-39014/22 government specification Shelf Life: N/a **Unit Of Measure:**

Fiig: A010b0

No

Demilitarization: