Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-254-0978

De du Stude
Body Style:
Piston
Overall Length:
0.651 inches
Terminal Length:
0.406 inches
Body Length:
0.281 inches
Overall Diameter:
0.145 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Center To Center Distance Between Mounting Facilities Parallel To Diameter:
0.125 inches
Quality Factor At 25 Deg Celsius:
7500.0
Terminal Width:
0.020 inches
Terminal Thickness:
0.010 inches
Inclosure Type:
Encased
Terminal Location:
Adjustment control end bent backward
Tuning Characteristic:
Straight line capacity single section
Adjustment Device Torque:
5.000 inch-ounces
Insulation Dc Resistance At Max Operating Temp:
100000.0 megohms
Mounting Facility Type And Quantity:
2 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Capacitance Range In Picofarads:
+0.6/+5.0 single section
Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw



Capacitance Drift In Picofarads:

0.02 single section

Material:

Ceramic base

Test Data Document:

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 ferrule and 1 printed circuit

Specification Data:

81349-mil-c-14409/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0