NSN 5910-01-256-1523

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-256-1523

view Offiline at https://defobasegroup.com/hsh/55/10-01-250-1525
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.236 inches
Body Length:
0.315 inches
Body Width:
0.295 inches
Body Height:
0.197 inches
Center To Center Distance Between Terminals Parallel To Length:
0.200 inches
Terminal Diameter:
0.024 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
1000.0 megohms
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 100.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
63.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-5.0/+5.0 single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
10000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
8.000
Terminal Surface Treatment:
Solder

Terminal Type And Quantity: 2 uninsulated wire lead

NSN 5910-01-256-1523

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0