NSN 5910-01-256-5084

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-256-5084

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
0.250 inches
Body Length:
0.135 inches
Body Width:
0.100 inches
Body Height:
0.110 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.200 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
90.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Tolerance Range Per Section:
-0.10/+0.10 picofarads single section
Case Material:
Ceramic
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 ribbon
Specification Data:
81349-mil-c-55681/5 government specification

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5910-01-256-5084

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0