NSN 5910-01-256-9588

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-256-9588 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.484 inches **Terminal Length:** 0.109 inches **Bushing Diameter:** 0.281 inches **Bushing Length:** 0.196 inches **Body Length:** 0.288 inches **Overall Diameter:** 0.281 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -25.0/+25.0 single section **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Terminal Location:** End opposite adjustment control perpendicular **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 0.500 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 64 **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches

NSN 5910-01-256-9588

Air Dielectric Variable Capacitor - Page 2 of 2



Capacitance Range In Picofarads:
+1.0/+14.0 single section
Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
1 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0