## NSN 5910-01-257-0132

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-257-0132 **Body Style:** Rotary **Terminal Length:** 3.9 millimeters **Overall Height:** 8.2 millimeters **Overall Diameter:** 7.0 millimeters Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -750.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 7.5 millimeters **Quality Factor At 25 Deg Celsius:** 500.0 **Terminal Width:** 1.2 millimeters **Inclosure Type: Encased Terminal Location:** Circumference on end opposite adjustment control perpendicular **Adjustment Device Torque:** Between 11.000 inch-ounces and 48.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 3 terminal **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +4.5/+20.0 single section **Nonderated Voltage Rating And Type:** 110.0 ac rms single section or 160.0 dc continuous single section Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: +1.75/+8.00 single section and -5.75/-1.75 single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Material: Metal base **Terminal Type And Quantity:** 3 printed circuit Shelf Life:

N/a

## NSN 5910-01-257-0132

Ceramic Dielectric Variable Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A096a0